CONTINUATION OF APPLN. NO. 09/647,614

REMARKS

The amendment to the specification corrects editorial errors contained in the Japanese language text as originally filed in the PCT application. The amendment to page 4 of the specification is supported by the paragraph bridging pages 4-5 of the specification, which clearly shows that the curable component is a urethane (meth)acrylate. The same is true of the amendment to page 5 of the specification.

Support for the new claims is found in original claims 1-4 and in the specification on pages 10-11.

Entry and consideration of this Amendment is respectfully requested.

Respectfully submitted,

Registration No. 40,641

SUGHRUE MION, PLLC 2100 Pennsylvania Avenue, N.W. Washington, D.C. 20037-3213

Telephone: (202) 293-7060 Facsimile: (202) 293-7860

Date: January 2, 2002

CONTINUATION OF APPLN. NO. '09/647,614

providing components of a hard disk drive assembly;

providing an ultraviolet-curing composition having a curable component; and

fixing or bonding components of said hard disk drive assembly using the ultravioletcuring composition,

wherein said curable component of said ultraviolet-curing composition is a urethane (meth)acrylate obtained by an addition reaction, using an organic zinc compound or an amine compound as a catalyst, between (1) an isocyanate group of an isocyanate oligomer, which is prepared by using an organic zinc compound or an amine compound as a catalyst in an addition reaction between an isocyanate group and an active hydrogen; and (2) a hydroxy group of a hydroxyalkyl (meth)acrylate.

6. (New) The method according to claim 5, wherein said urethane (meth)acrylate is a product of an addition reaction, using an organic zinc compound or an amine compound as a catalyst, between:

an isocyanate group of an isocyanate oligomer, which is prepared, by using an organic zinc compound or an amine compound, from a polyether having a hydroxy group at a terminal thereof and an isocyanate compound having two or more isocyanate groups per molecule; and a hydroxy group of a hydroxyalkyl (meth)acrylate,

wherein no tin compound is used as a catalyst in these two addition reactions.

7. (New) The method according to claim 5, wherein the urethane (meth)acrylate, which is a main component of said ultraviolet-curing composition, is a product of an addition reaction, using an organic zinc compound or an amine compound as a catalyst, between:

an isocyanate group of an isocyanate oligomer, which is prepared, by using an organic zinc compound or an amine compound, from a polyester having a hydroxy group at a terminal or

CONTINUATION OF APPLN. NO. 09/647,614

in a side chain thereof and an isocyanate compound having two or more isocyanate groups per molecule; and

a hydroxy group of a hydroxyalkyl (meth)acrylate,
wherein no tin compound is used as a catalyst in these two addition reactions.

8. (New) The method according to claim 5,

wherein the polyurethane (meth)acrylate, which is a main component of said ultravioletcuring composition, is a product of an addition reaction, using an organic zinc compound or an amine compound as a catalyst, between:

an isocyanate group of a polyether/polyester copolymerized isocyanate oligomer

compound, which is prepared by an addition reaction among a polyester having a hydroxy group

at a terminal or in a side chain thereof, a polyether having a hydroxy group at a terminal thereof,

and a diisocyanate compound having two or more isocyanate groups per molecule; and a

hydroxy group of a hydroxyalkyl (meth)acrylate,

wherein no tin compound is used as a catalyst in these two addition reactions.

9. (New) The method according to claim 5, wherein the ultraviolet-curing

composition forms a flange gasket of a hard disk drive housing case.

10. (New) The method according to claim 5, wherein the ultraviolet-curing

composition fixes a cap seal to a hard disk drive spindle motor.

11. (New) The method according to claim 5, wherein the ultraviolet-curing

composition fixes a magnetic head of a hard disk drive to a supporting arm.

12. (New) The method according to claim 5, wherein the ultraviolet-curing

composition fixes a packing or packings in a housing case of a hard disk drive assembly.

CONTINUATION OF APPLN. NO. 09/647,614

13. (New) The method according to claim 5, wherein the ultraviolet-curing
composition bonds substrates to connectors in the hard disk drive assembly.
14. (New) The method according to claim 5, wherein the hard disk drive assembly
comprises at least the following components:
a hard disk for storing data;
a spindle motor for rotating the hard disk;
a cap seal affixed to the spindle motor;
a movable read/write magnetic head or heads positioned relative to the hard disk such
that data may be written on or read from the hard disk using the magnetic head;

and a housing case for the hard disk, the spindle motor and the magnetic head.